

Package: DominoDataR (via r-universe)

September 13, 2024

Title 'Domino Data R SDK'

Version 0.2.4

Description A wrapper on top of the 'Domino Data Python SDK' library.

It lets you query and access 'Domino Data Sources' directly from your R environment. Under the hood, 'Domino Data R SDK' leverages the API provided by the 'Domino Data Python SDK', which must be installed as a prerequisite. 'Domino' is a platform that makes it easy to run your code on scalable hardware, with integrated version control and collaboration features designed for analytical workflows. See https://docs.dominodatalab.com/en/latest/api_guide/140b48/domino-data-api for more information.

License Apache License (>= 2)

URL <https://github.com/dominodatalab/DominoDataR>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports arrow, ConfigParser, httr, reticulate, urltools, withr

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Gabriel Haim [aut, cre]

Maintainer Gabriel Haim <gabriel.haim@dominodatalab.com>

Repository <https://dominodatalab.r-universe.dev>

RemoteUrl <https://github.com/dominodatalab/dominodatar>

RemoteRef HEAD

RemoteSha c154e687893a1141d0d9e982e13645db2b7000b2

Contents

add_credentials	2
add_override	3
datasource_client	3
get_object	4
list_keys	4
load_aws_credentials	5
load_oauth_credentials	5
object_http	6
put_object	7
py_domino_data_install	7
py_select_interpreter	8
query	8
save_object	9
upload_object	9

Index	11
--------------	-----------

add_credentials	<i>Add credentials override for the right datasources</i>
-----------------	---

Description

Add credentials override for the right datasources

Usage

```
add_credentials(auth_type, config = list())
```

Arguments

auth_type	Datasource Authentication type
config	existing config override to extend

Value

named list of override configuration values

add_override	<i>Add override configuration values</i>
--------------	--

Description

Add override configuration values

Usage

```
add_override(..., .override = character())
```

Arguments

...	named configuration values.
.override	a named character vector

Value

named list of override configuration values

datasource_client	<i>Create a client to Domino datasources</i>
-------------------	--

Description

Create a client to Domino datasources

Usage

```
datasource_client(api_key = NULL, token_file = NULL)
```

Arguments

api_key	string key to override the environment variable
token_file	location of file to read token from

Value

A `domino_data.data_sources.DataSourceClient`.

get_object	<i>Retrieve an object from a datasource</i>
------------	---

Description

Retrieve an object from a datasource

Usage

```
get_object(client, datasource, object, as = "raw", override = list())
```

Arguments

client	As returned by datasource_client()
datasource	The name of the datasource to query
object	The object to retrieve
as	Passed through to content
override	Configuration values to override (add_override())

Value

Raw vector representation of the object

list_keys	<i>List the keys starting with prefix in an object store</i>
-----------	--

Description

List the keys starting with prefix in an object store

Usage

```
list_keys(client, datasource, prefix = "", override = list(), page_size = 50)
```

Arguments

client	As returned by datasource_client()
datasource	The name of the datasource to query
prefix	Prefix to filter keys to list
override	Configuration values to override (add_override())
page_size	Number of objects to fetch

Value

A vector or string keys

load_aws_credentials *Load AWS Credentials*

Description

Load AWS Credentials

Usage

```
load_aws_credentials(location, profile = NULL)
```

Arguments

location	file path where AWS credentials are located
profile	AWS profile or section to use

Value

named list of override configuration values

load_oauth_credentials
Load OAuth Credentials

Description

Load OAuth Credentials

Usage

```
load_oauth_credentials(location)
```

Arguments

location	file path where token is located
----------	----------------------------------

Value

named list of override configuration values

object_http	<i>HTTP requests for Object Stores</i>
-------------	--

Description

HTTP requests for Object Stores

Usage

```
object_http(  
  verb = "GET",  
  url,  
  datasource_type,  
  config = list(),  
  headers = list(),  
  request_body = "",  
  write_disk = NULL  
)
```

Arguments

verb	A character string containing an HTTP verb, defaulting to "GET".
url	Signed URL to download object at.
datasource_type	Type of datasource the object is stored in.
config	A list of config values for the REST call.
headers	A list of request headers for the REST call.
request_body	A character string containing request body data.
write_disk	An argument like write_disk to write the result directly to disk.

Details

This is mostly for internal use by object store APIs.

Value

a [response](#) object.

put_object	<i>Upload an object to a datasource</i>
------------	---

Description

Upload an object to a datasource

Usage

```
put_object(client, datasource, object, what, override = list())
```

Arguments

client	As returned by datasource_client()
datasource	The name of the datasource to query
object	The object to retrieve
what	character vector, raw vector
override	Configuration values to override (add_override())

Value

Raw vector representation of the object

py_domino_data_install	<i>Install domino_data Python package</i>
------------------------	---

Description

Install domino_data Python package

Usage

```
py_domino_data_install(version)
```

Arguments

version	Version of the domino_data package to install.
---------	--

Value

TRUE if installation was successful, FALSE otherwise.

`py_select_interpreter` *Tell reticulate to use Python Conda version available on Domino Data Lab.*

Description

Provide other options in case the package is used for local development.

Usage

```
py_select_interpreter()
```

Value

TRUE if a python binary was bound to reticulate, FALSE otherwise

`query` *Query a datasource and returns an arrow Table*

Description

Query a datasource and returns an arrow Table

Usage

```
query(client, datasource, query, override = list())
```

Arguments

<code>client</code>	As returned by datasource_client()
<code>datasource</code>	The name of the datasource to query
<code>query</code>	The query to run against the provided datasource
<code>override</code>	Configuration values to override (add_override())

Value

An [arrow::Table](#)

save_object	<i>Save an object from a datasource to a local file</i>
-------------	---

Description

Save an object from a datasource to a local file

Usage

```
save_object(  
  client,  
  datasource,  
  object,  
  file = basename(object),  
  override = list()  
)
```

Arguments

client	As returned by datasource_client()
datasource	The name of the datasource to query
object	The object to retrieve
file	File path to save object at. Defaults to the object base name.
override	Configuration values to override (add_override())

Value

Raw vector representation of the object

upload_object	<i>Upload a file to a datasource</i>
---------------	--------------------------------------

Description

Upload a file to a datasource

Usage

```
upload_object(client, datasource, object, file, override = list())
```

Arguments

client	As returned by datasource_client()
datasource	The name of the datasource to query
object	The object to retrieve
file	File path to upload..
override	Configuration values to override (add_override())

Value

Raw vector representation of the object

Index

add_credentials, 2
add_override, 3
add_override(), 4, 7–10
arrow::Table, 8

content, 4

datasource_client, 3
datasource_client(), 4, 7–10

get_object, 4

list_keys, 4
load_aws_credentials, 5
load_oauth_credentials, 5

object_http, 6

put_object, 7
py_domino_data_install, 7
py_select_interpreter, 8

query, 8

response, 6

save_object, 9

upload_object, 9

write_disk, 6